

DIP2MADW-28 / DIP2MBW-36

2 Megapixel 1080P IP / Megapixel Wireless Cameras



Features

- 1/3" 3 Megapixel progressive CMOS
- H.264 & MJPEG dual-stream encoding
- 25/30fps @1080P (1920×1080)
- DWDR, Day/Night(ICR), AWB, AGC, BLC
- Multiple network monitoring
- 2.8mm / 3.6mm fixed lens
- Max. IR LEDs Length 30m / 98 ft
- Wi-Fi Support
- IP66, PoE



DIP2MADW-28



DIP2MBW-36

Specifications

		DIP2MADW-28	DIP2MBW-36
Image Sensor		1/3" 3 Megapixel Aptina CMOS	
Resolution		3M (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) / CIF(352×288/352×240)	
Frame Rate	Main Stream	1080P / 720P (1 ~ 25/30fps)	
	Sub Stream	D1/CIF (1~30fps)	
Bit Rate		H.264: 16K ~ 8192Kbps	
Electronic Shutter		Auto / Manual ; 1/4 ~ 1/100,000s	
Effective Picture (H × V)		2048 x 1536	
Focal Length / Max Aperture		2.8mm	3.6mm (Fixed) / F1.8
Lens Mount Type		Board-in Type	
Min. Illumination Color / B&W		Color: 0.1 Lux / F1.8 B&W: 0 Lux / F1.8	Color: 0.1 Lux / F1.6 B&W: 0.005 Lux / F1.6
Infrared Range		98ft. (Max.)	
Day / Night		Auto (ICR) / B&W / Color	
Backlight Compensation		BLC / HLC / DWDR	
White Balance		Auto / Manual	
Gain Control		Auto / Manual	
Noise Reduction		3D	
Privacy Masking		Up to 4 Areas	
Angle of View		H: 90°	H: 72.5°
Network		RJ45 (1/100Base-T)	
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
Compatibility		ONVIF, PSIA, CGI	
Max User Access		20 Users	
Weatherproof Rating		IP66	
Wireless		Wi-Fi(802.11b/g/n)	Wi-Fi (IEEE802.11b/g/n)
Power Supply		DC 12V, PoE (802.3af)	
Working Environment		-22°~140° F (-30°~ 60° C), 10%~90% RH	
Dimensions / Weight		4.33" × 3.2" / 1 lb (0.39 kg)	2.76" × 2.6" × 6.1" / 1 lb (.42 kg)