

## DHDD3MA

3 Megapixel IP / Network Armor Dome Camera



### Features

- 3 Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- 20fps @ 3MP (2048 x 1536), 25/30fps @ 1080P (1920x1080)
- DWDR, Day/Night, 3DDNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens
- Micro SD memory, IP66, IK10, PoE



### Specifications

		DHDD3MA
Image Sensor		1/3" 3 MegaPixel Exmor CMOS
Resolution		3M (2048x1536) / 1080P (1920x1080) / 720P (1280x720) / D1 (704x480) / CIF (352x240)
Frame Rate	Main Stream	3M (1~20fps) / 1080P/720P (1~30fps)
	Sub Stream	D1/CIF (1~30fps)
Bit Rate		H.264: 32~8,192 Kbps   MJPEG: 32~20,480 Kbps
Electronic Shutter		Auto / Manual ; 1/4 ~ 1/100,000s
Effective Picture (H x V)		2048 x 1536
Focal Length		2.8mm Lens
Lens Mount Type		Board-in Type
Min. Illumination		Color: 0.1 Lux @ F1.8
Infrared Range		65ft. (Max.)
Day / Night		Auto (ICR) / B&W / Color
Backlight Compensation		BLC / HLC / DWDR
White Balance		Auto / Manual
Gain Control		Auto / Manual
Noise Reduction		3D
Privacy Masking		Up to 4 Areas
Angle of View		H: 72.5°
Network		1 x RJ45 Ethernet port (10/100 Mbps)
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility		ONVIF 2.0
Max User Access		20 Users
Memory Slot		Micro SD - Max 64GB
Weatherproof Rating		IP66
Power Supply		DC 12V, PoE (802.3af) / < 2.5W
Working Environment		14°~140° F (-10°~ 60° C), 10%~90% RH
Dimensions / Weight		4.3" x 2.13" (110 x 54mm) / 0.55 lb (0.25 kg)